

BUILT
TO LAST
PERFORMANCE

MORITZ ELX GT SERIES

DLH SERIES



ELH AR SERIES



ELH GT SERIES



ELH HT SERIES



FDH DT SERIES



FDH HT SERIES



TBA SERIES



TB SERIES



Trust in the LORD with all thine heart; and lean not unto thine own understanding. Proverbs 3:5 KJV

STANDARD SPECIFICATIONS

gravity tilt deck	16' long
stationary deck	20' model - 4' long 22' model - 6' long 24' model - 8' long
deck height	approximately 26"
deck loading angle	approximately 13 degrees
between fenders	82"
frame	10" I-beam
stake pockets	3" x 1/4" formed bar
tool box	1/8" large steel diamond plate
fenders	1/8" steel diamond plate
suspension	rubber ride (low maintenance)
brakes	electric (all wheels)
tires & wheels	22900 lb GVWR - 17.5" 16 ply rated 8 bolt 25900 lb GVWR - 17.5" 18 ply rated 8 bolt
jack	15000 lb
coupler	2-5/16" (25,000lbs on 22,900lb gvwr)
pintle ring	21 ton
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty (see warranty for details)	

OPTIONS

winch mount
hydraulic jack
pintle ring (standard on 25,900 gvwr)
pallet fork holder
solar panel (with hydraulic jack)
spare tire & wheel

COLORS

black - red - charcoal

FRAME SPECIFICATIONS

frame & tongue	cross members
10" I-beam	3" channel on 12" centers
fenders	Tilt Deck
1/8" steel diamond plate	5"x5"x1/4" tube runners

AXLE SPECIFICATIONS *(rubber ride suspension)*

GVWR	axles
22900 lb	10,000 lb with electric brakes & easy lube spindles
25900 lb	12,000 lb with electric brakes & easy lube spindles

