

MORITZ

FDH DT SERIES

Pintle Ring



The Lord is my strength and song, And He has become my salvation. Psalm 118:14 KJV

BUILT
TO LAST
PERFORMANCE

DLH SERIES



ELH AR SERIES



ELH GT SERIES




ELH HT SERIES



FDH DT SERIES



FDH HT SERIES



TBA SERIES



TB SERIES



STANDARD FEATURES

tongue	HD I-beam tongue
nose plate	one piece formed plate
chassis	torque chassis (<i>torque resistant cross tubes</i>) cambered main beams pierced main beams
dovetail & ramps	steel dozer ramps adjustable spring tension 12-1/2 degree loading angle increased ground clearance dovetail HD fade away hinge system ramp hold down latch (<i>to deck</i>) vertical ramp bars 5' self cleaning dovetail
deck	low profile - 33" high 102" wide cross sills - 16" center (<i>24" center 15,900 gvwr</i>) side rails - 6"@8.2 lb/ft channel stake pockets - 3" x 1/4" rub rail - 2" x 5/16" extra running lights pipe spools
tool box	extra large steel diamond plate light inside tool box addition storage infront of toolbox
suspension	7k & 8k axles - torsion 10k & 12k axles - spring
brakes	electric
tires & wheels	ST235/80 R16 LRE
jack	dual 15k
pintle ring	21 ton
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty (<i>see warranty for details</i>)	

prototype photos - some details may change on production version



OPTIONS

under body tool box	disc brakes with electric over hydraulic brakes
dual two speed jacks	solar charger (<i>for use with hydraulic jacks</i>)
dual hydraulic jacks	spare tire & wheel
winch - 12000 lb	ultimate ramps
electric over hydraulic brakes (<i>drum brakes</i>)	COLORS black - red - charcoal

SPECIFICATIONS BY GVWR

GVWR	Main Beams	Axles	Tires & Wheels
15900	12" @ 14 lb/ft	2 - 7k torsion	ST235/80R 16 LRE single
17900	12" @ 14 lb/ft	2 - 8k torsion	LT215/75R 17.5 LRH single
22900	14" @ 22 lb/ft	2 - 10k spring	ST235/80R 16 LRE dual
25900	14" @ 22 lb/ft	2 - 12k spring	ST235/80R 16 LRE dual