

MORITZ

FDH DT SERIES



Trust in the LORD with all thine heart; and lean not unto thine own understanding. Proverbs 3:5 KJV

BUILT
TO LAST
PERFORMANCE

DLH SERIES



ELH AR SERIES



ELH GT SERIES



ELH HT SERIES



FDH DT SERIES



FDH HT SERIES



TBA SERIES



TB SERIES



STANDARD FEATURES

gooseneck	proprietary HD gooseneck design
winch mount	standard on all goosenecks
chassis	torque chassis <i>(torque resistant cross tubes)</i> cambered main beams pierced main beams
dovetail & ramps	aluminum wedge ramps adjustable spring tension 12-1/2 degree loading angle increased ground clearance dovetail HD fade away hinge system ramp hold down latch <i>(to deck)</i> vertical ramp bars
deck	5' self cleaning dovetail low profile - 33" high 102" wide cross sills - 16" center <i>(24" center 15,900 gvwr)</i> side rails - 6"@8.2 lb/ft channel stake pockets - 3" x 1/4" rub rail - 2" x 5/16" extra running lights pipe spools
tool box	extra large steel diamond plate light inside tool box chain rack inside tool box
suspension	7k & 8k axles - torsion 10k & 12k axles - spring
brakes	electric
tires & wheels	ST235/80 R16 LRE
jack	dual 15k
coupler	2-5/16" adjustable
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty <i>(see warranty for details)</i>	

prototype photos - some details may change on production version



OPTIONS

under body tool box	disc brakes with electric over hydraulic brakes
dual two speed jacks	solar charger <i>(for use with hydraulic jacks)</i>
dual hydraulic jacks	spare tire & wheel
winch - 12000 lb	dozer ramps
electric over hydraulic brakes <i>(drum brakes)</i>	COLORS black - red - charcoal

SPECIFICATIONS BY GVWR

GVWR	Main Beams	Axles	Tires & Wheels
15900	12" @ 14 lb/ft	2 - 7k torsion	ST235/80R 16 LRE single
17900	12" @ 14 lb/ft	2 - 8k torsion	LT215/75R 17.5 LRH single
22900	14" @ 22 lb/ft	2 - 10k spring	ST235/80R 16 LRE dual
25900	14" @ 22 lb/ft	2 - 12k spring	ST235/80R 16 LRE dual